

Next Generation Real Time Solar Wind (RTSW) Energetic Particle Detector



Fundamental Question:

What energetic particle observation is required for the next generation RTSW system?

Why is the question important:

Space weather forecasting requires specific observations for model inputs.

Science Objectives:

- Energetic ion and electron observations are used in modeling efforts to predict the arrival of Energetic Storm Particle (ESP) events.
- Advanced space weather forecasting requires detailed angular, spectral, and compositional observations.
- The next generation RTSW Energetic particle detector must make these key observations

Mission Description:

- •Observations from a spinning spacecraft that stations well upstream of the Earth, as well as additional inner-heliospheric missions
- •Continuous telemetry coverage
- •Entire payload consists of magnetic field, plasma, and energetic particle instruments


Measurement Strategy:

- •Total ion measurements with good angular and energy resolution
- •Elemental composition measurements
- •Electron measurements with good angular and temporal resolution
- •One minute temporal resolution
- •12 seconds spin rate
- •One high energy telescope that measures E>10 MeV and E>30 MeV ion

Technology Requirement:

- •Low power, low mass time-of-flight circuitry
- •Low power, low mass integrated energy circuitry
- •Good angular and temporal coverage compact energetic electron detector
- •Onboard automatic spacecraft processing to reduce Earth-based data handling and analysis requirements

Technical description of the Next Generation RTSW energetic particle detector



Energetic Particle Detector

Telemetry requirements for the EPD

Species	# detectors	# channels	# sectors	# words
Electrons	12	4	12	576
Protons	6	5	12	360
Не	6	5	1	30
CNO	6	5	1	30
Fe	6	5	1	30
High E ions	2	2	1	4

Ion and Composition detection

- •One 6 sectors time-of-flight ion detector covering 4π sr when the spacecraft spin is included
- •Total ion detector system uses <1 Watt of power and <1 kg
- •Energy range is (0.02 < E < 5) MeV

Electron detection

- •One 12 sectors magnetically deflected electron detector mounted similar to the ion detector
- •Total electron system uses ~1/2 Watt of power
- •Magnetically deflected electron system measures electrons from (30 < E < 350) keV

High Energy telescope

- •Simple SSD stack with appropriate absorbers, adjusted to return the required energy coverage
- •Energy coverage from (5 < E < 30) MeV

This robust system requires only ~50 bytes/sec (16 bit words), similar to the current RTSW downlink. This would need to be expanded to include the plasma and magnetic field observations